


DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq Yd:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Tufted Pile Weight:	22 oz/yd ² (746 g/m ²)
Finished Pile Thickness:	.088" (2.23 mm)
Stitches Per Inch:	10.0 (39.37 per 10 cm)
Dye Method:	Solution Dyed
Fiber Type:	Colorstrand® SD Nylon
Stain Release Technology:	EcoSentry Plus Stain Protection
Soil Release Technology:	EcoSentry Soil Protection
Density:	9,000
Weight Density:	198,000
Backing Material:	EcoFlex NXT
Alternate Backing:	EcoFlex AIR - Minimum SY Required
Installation Method:	Quarter Turn, Vertical Ashlar, Brick Ashlar, Monolithic, Multi Directional
Size:	24" x 24" (.6096 m x .6096 m)
Pattern Repeat:	Not Applicable



556
Foremost
Quickship Available



727
Priority
Quickship Available



848
Beginning
Quickship Available



869
Immediate
Quickship Available



959
Preference
Quickship Available



988
Importance
Quickship Available

SUSTAINABILITY

Pre-Consumer Recycled Content:	48%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Indoor Air Quality:	CRI Green Label Plus GLP1171
Declare Label:	Declared Red List Free

PERFORMANCE

Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
Foot Traffic Recommendation TARR:	Severe

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static, 10 Year Colorfastness to Atmospheric Contaminants
-------------	---